

Tubolari

Fornitura standard

Barre di lunghezza commerciale di 6.000 mm.

Fornitura flessibile

Barre da 3.000 mm a 12.000 mm oppure tagliate su misura fino a una lunghezza minima di 50 mm.

Elenco prodotti

Tubi saldati tondi, rettangolari, quadri, ovali e semiovali.

Campi di applicazione

Ponteggi per edilizia
Carpenteria
Segnaletica stradale
Serre per agricoltura
Mobilio
Fotovoltaico
Scaffalature
Grigliato elettrofuso

Standard Supply

Standard size supply with bars of commercial length 6 mt.

Versatile Supply

Versatile Supply, bars from 3 mt till 12 mt or cut on request till 50 mm length.

List of products

Round, rectangular, square, oval and semi-oval welded tubes.

Fields of application

Scaffolding For Building Construction, General Carpentry, Roadsigns, Greenhouses, Furniture Tubes, Photovoltaic, Scaffolding, Electro-Fused Steel Grating Panel

Tubes



TUBI SALDATI TONDI

ROUND WELDED TUBES

peso in kg per metro lineare / kg weight per linear meter

	SPESSORI / THICKNESS (mm)											
	0,8	1,0	1,2	1,5	1,8	2,0	2,3	2,5	2,7	3,0	4,0	
Ø DIAMETRI / DIAMETER (mm)	16	0,33	0,40	0,48	0,60							
	18	0,37	0,46	0,55	0,68	0,81	0,89					
	20	0,40	0,49	0,59	0,73	0,88	0,97					
	21	0,43	0,53	0,64	0,79	0,93	1,04	1,19				
	22	0,44	0,55	0,65	0,81	0,97	1,07	1,21				
	25	0,51	0,63	0,75	0,94	1,12	1,24	1,41				
	26,75	0,53	0,67	0,80	0,98	1,17	1,30	1,50	1,63	1,74	1,91	
	28,7	0,57	0,72	0,86	1,07	1,28	1,41	1,59	1,73	1,85		
	30	0,60	0,75	0,88	1,11	1,32	1,46	1,68				
	32	0,65	0,80	0,96	1,19	1,43	1,58	1,82	1,94	2,10	2,28	
	33	0,67	0,83	0,99	1,25	1,47	1,63	1,88	2,03	2,18	2,42	
	33,8	0,68	0,85	1,02	1,26	1,50	1,66	1,89	2,05	2,19	2,43	
	35	0,71	0,87	1,05	1,31	1,55	1,73	1,96	2,13	2,28		
	38	0,77	0,96	1,15	1,44	1,71	1,90	2,17	2,34	2,53	2,75	3,64
	40	0,80	0,99	1,20	1,48	1,78	1,98	2,26	2,43	2,61	2,90	3,83
	42,5	0,83	1,04	1,24	1,54	1,84	2,04	2,35	2,53	2,73	3,04	4,02
	45		1,10	1,33	1,64	1,96	2,18	2,49	2,71	2,90	3,23	4,27
	48		1,18	1,41	1,75	2,10	2,32	2,67	2,90	3,12	3,46	4,64
	48,4 ^{sc}				1,79	2,16	2,36	2,74	2,93	3,02	3,55	
	50		1,24	1,47	1,83	2,19	2,48	2,84	3,08	3,31	3,67	4,86
	51		1,24	1,51	1,87	2,23	2,48	2,84	3,08	3,31	3,67	
	54			1,99	2,39	2,64	3,04	3,29	3,55	3,90	4,00	5,30
	55				2,02	2,42	2,68					
	56				2,06	2,46	2,73					
	57				2,09	2,51	2,79	3,14	3,45		4,12	
	60			1,76	2,20	2,63	2,92	3,35	3,65	3,94	4,36	5,77
	60 ^{sc}					2,69	2,99	3,44	3,74	4,00		
	63				2,33	2,78	3,09		3,85	4,15	4,59	6,09
70				2,58	3,08	3,41		4,26		5,11		
76			2,27	2,84	3,36	3,72		4,63	5,53	7,35		
89					3,93	4,35	5,02	5,44	6,52	8,67	8,66	
95					4,20	4,65	5,34	5,81	6,26	6,95	9,26	
102					4,51	4,99	5,74	6,24	6,74	7,46	9,92	



**TUBI
SALDATI
TONDI**

*ROUND
WELDED
TUBE*

NORME DI RIFERIMENTO

REFERENCE RULES

		NORMATIVE / RULES
QUALITÀ / MATERIALS	CALDO HOT ROLLED STEEL COILS	
	S185 S235JR/JR+M S275 S355 S430	EN 10025 EN 10219
	ZINCATO GALVANISED STEEL COILS	
	DX51D+Z S250 S280 S350GD+Z	EN 10143 EN 10219
	FREDDO COLD ROLLED STEEL COILS	
	DC01	EN 10130 EN 10219
	DECAPATO PICKLED STEEL COILS	
	DD11	EN 10111 EN 10219